

Y69 IND-4

Developed for loaders, container handlers and port equipment.

Heavy loads, tight vehicle maneuvers, and continuous operations are the ideal conditions to showcase Yokohama ingenuity. Our specialized tires for ports and railyards are engineered to excel in these uniquely abusive environments, so your productivity can be maximized every day.



- Thicker tread provides added scrub resistance
- ID Spec features reinforced sidewalls and bead area to carry heavy loads
- Exceptional compound designed for port applications for longer hours of operation
- Outstanding retreadability
- Lower cost-per-hour



Size	Part #	Compound	Ply	Groove Depth	Rim Size	Overall Diameter (inches)	Overall Width (inches)	Static Loaded Radius (inches)	Static Loaded Width (inches)	Ship Weight
12.00-24	06913	ID	20	56	8.50VX24	49.4	12.9	23.2	13.7	356.91
14.00-24	06914	ID	30	58	1000WX24	53.7	15.4	25.6	15.9	469.40
16.00-25	06919	ID	32	53	11.25X25-2.0	60.4	17.2	27.9	18.7	683.68
18.00-25	06936	ID/CPC	32	74	13.00X25-2.5	64.5	21.1	29.7	22.5	918.00
18.00-25	06915	ID	40	74	13.00X25-2.5	64.5	21.1	29.7	22.5	1,003.10
18.00-25	06940	ID	40	74	13.00X25-2.5	64.5	21.1	29.7	22.5	1,008.16
*18.00-33	06977	ID	40	74	33X13.00-2.5	73.5	20.2	33.2	22.2	1,175.39
21.00-25	06972	ID	40	71	15.00X25-3.0	70.1	23.5	31.3	25.4	1,170.17
21.00-35	06917	ID/CPC	42	81	15.00X35-3	80.2	23.6	36.2	25.6	1,574.50

Technical information subject to change without notice.